

Uniflow® Stringwound Sediment Cartridges

The Uniflow range of Stringwound Sediment Cartridges offer excellent dirt holding capacity and are ideal for use as a pre-filter or stand-alone filter in high sediment applications.

Uniflow Stringwound Sediment Cartridges are wound in a precise pattern around the core to provide a greater surface area for higher flow rates. These cartridges have a proven record of consistent filtration performance and offer broad chemical compatibility and good temperature resistance.

These cartridges effectively reduce dirt, rust, scale and sediment. Designed to suit a wide range of industry standard housings, these cartridges are ideal for both pre-filtration and final-stage filtration applications.

Benefits

- High dirt holding capacity
- Broad chemical compatibility
- Flow rates up to 160LPM
- Lengths - 10", 20", 30", 40"
- Ratings - 0.5 - 160* Micron

Applications

- Drinking water
- Food & Beverage
- Pre and post-filtration
- Commercial & Industrial
- Water Treatment



Order Code	Size (Inches)	Rating (Nominal)	Flow (LPM)	Description
FSW-1025-0.5	10" x 2.5"	0.5 Micron	25	Stringwound Sediment Cartridge - Standard Diameter (Cyst Reduction)
FSW-1025-1	10" x 2.5"	1 Micron	26	Stringwound Sediment Cartridge - Standard Diameter
FSW-1025-5	10" x 2.5"	5 Micron	27	Stringwound Sediment Cartridge - Standard Diameter
FSW-1025-10	10" x 2.5"	10 Micron	32	Stringwound Sediment Cartridge - Standard Diameter
FSW-1025-20	10" x 2.5"	20 Micron	38	Stringwound Sediment Cartridge - Standard Diameter
FSW-2025-1	20" x 2.5"	1 Micron	52	Stringwound Sediment Cartridge - Standard Diameter
FSW-2025-5	20" x 2.5"	5 Micron	54	Stringwound Sediment Cartridge - Standard Diameter
FSW-2025-10	20" x 2.5"	10 Micron	64	Stringwound Sediment Cartridge - Standard Diameter
FSW-2025-20	20" x 2.5"	20 Micron	76	Stringwound Sediment Cartridge - Standard Diameter
FSW-3025-1	30" x 2.5"	1 Micron	75	Stringwound Sediment Cartridge - Standard Diameter
FSW-3025-5	30" x 2.5"	5 Micron	81	Stringwound Sediment Cartridge - Standard Diameter
FSW-4025-1	40" x 2.5"	1 Micron	104	Stringwound Sediment Cartridge - Standard Diameter
FSW-4025-5	40" x 2.5"	5 Micron	108	Stringwound Sediment Cartridge - Standard Diameter
FSW-1045-1	10" x 4.5"	1 Micron	75	Stringwound Sediment Cartridge - Large Diameter
FSW-1045-5	10" x 4.5"	5 Micron	76	Stringwound Sediment Cartridge - Large Diameter
FSW-1045-10	10" x 4.5"	10 Micron	79	Stringwound Sediment Cartridge - Large Diameter
FSW-1045-20	10" x 4.5"	20 Micron	82	Stringwound Sediment Cartridge - Large Diameter
FSW-2045-1	20" x 4.5"	1 Micron	150	Stringwound Sediment Cartridge - Large Diameter
FSW-2045-5	20" x 4.5"	5 Micron	152	Stringwound Sediment Cartridge - Large Diameter
FSW-2045-10	20" x 4.5"	10 Micron	158	Stringwound Sediment Cartridge - Large Diameter
FSW-2045-20	20" x 4.5"	20 Micron	160	Stringwound Sediment Cartridge - Large Diameter

*Other sizes and micron ratings are available. Please contact our technical sales team on 1800 446 500.

Please note: Flow rates are indicative only. Use only with microbiologically safe and adequately disinfected water supplies.