



# ZIP HYDROTAP G5 BC20 CLASSIC CHROME



BOILING



CHILLED

FILTERED

## Order Code H51702Z00AU

Zip HydroTap Boiling, Chilled, Filtered water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including 2 boiling water safety modes, 3 energy saving modes including ON/OFF timers and sensor activated 'sleep when it's dark', 'Quiet' mode with automated intelligent fan speed adjustment, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, and 0.2 micron water filtration.



Manufacturing Code	H51702Z00AU
--------------------	-------------

Capacity	Commercial
----------	------------

Boiling Cups per hour	100
-----------------------	-----

Chilled Cups per hour	75
-----------------------	----

Tap	Zip HydroTap CLASSIC Tap (Chrome)
-----	-----------------------------------

Water Pressure	Min 170kPa - Max 700kPa
----------------	-------------------------

Water Connection	1/2" BSP (G1/2)
------------------	-----------------

Water Supply Requirements	Cold
---------------------------	------

Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve
--------------	--

Power Rating	1.9kW 220-240V 50Hz
--------------	---------------------

Power Supply	1 x 10 Amp socket outlet
--------------	--------------------------

Dimensions	W280mm x D455mm x H333mm
------------	--------------------------

Product Approvals	WaterMark, RCM, ARC
-------------------	---------------------


Installation Requirements

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product.3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.6. Installation by Zip Professional Service can be arranged with a phone call or through [www.zipwater.com](http://www.zipwater.com)

Installation Detail

**Ventilation requirements** Contact your local service provider if ventilation is not suitable


**Clearance envelope**  
Position the Tap and the Command Centre as close together as possible.



200  
333  
50  
Command Centre width

**HydroTap Tap options**


Classic Plus  
Classic  
Elite Plus  
Touch-Free Wave



116  
216  
126  
116  
208  
126  
116  
221  
134  
116  
214  
126  
100  
100mm clearance envelope required. For Sink installations, install on the left-hand side of the Sink for ease of access to Boiling water function.


**Font options**

**Raised Font**  
with 135mm Extension  
part no. 95258



116  
280  
351  
116  
258  
20


**Font**  
with 135mm Extension  
part no. 90915



116  
280  
351  
116  
219  
104  
6

**Tap Positioning**  
Position the Tap to dispense into the sink, allowing clearance for a cup or teapot. Alternatively, mount the HydroTap Tap on a Font (available as an accessory).


35mm hole for HydroTap Tap



Sink

**Cutting detail**


108 hole for bowl  
10 hole for M6 stud  
86 hole for bowl  
35 hole for tap  
219



108  
10  
86  
35  
219

**Cutting detail**

108 hole for bowl  
10 hole for M6 stud  
86 hole for bowl  
35 hole for tap  
219



108  
10  
86  
35  
219

**4mm buffer pad air space**



4mm buffer pad air space

**Classic Plus Tap**

216



200 min.  
333  
50 min.  
280  
50 min.

**Clearance Envelope**

200 min.  
333  
50 min.  
280  
50 min.

**Clearance Envelope**

455

**IEC Flex & Plug**  
230-240V, 50Hz  
power outlet

**Air inlet grille**

**Mains cold water isolation valve**  
(not supplied)

**SCALE 1:5**

**ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.**

**HydroTap G5  
BC20**

shown with "Classic Plus" Tap

