

## Pentair Standard Filter Housings

Pentair filter housings are known for their high quality, performance and economy. Offering a comprehensive range of vessels, they are suitable for many standard and specialist applications.

Manufactured from FDA approved polypropylene materials, these housings suit standard 10" and 20" double-open-end cartridges for sediment, carbon and specialist types.

Housings can be manifolded together to achieve multiple treatment phases and a range of accessories are available.

Maximum Temperature: 52°C

Maximum Pressure: 8.6 bar

### Benefits

- Compact & economical
- Available in 10" and 20"
- Suit a wide range of standard cartridges
- Range of connections from ¼" to ¾"

### Applications

- Point-of-Entry Filtration
- Drinking Water
- Food Service
- Point-of-use filtration
- Rainwater Filtration



Order Code	Size	Connection	Description	Flow (LPM)
FHG-1025-14	10"	¼"	White 10" Hosing - ¼" NPT	12
FHG-1025-12	10"	½"	Blue 10" Housing - ½" BSP	35
FHG-1025-12-PR	10"	½"	Blue 10" Housing - ½" BSP with pressure release	35
FHG-1025-34	10"	¾"	White 10" Housing - ¾" BSP	38
FHG-2025-34	20"	¾"	Blue 20" Housing - ¾" BSP	76
<b>Bracket Kit - Includes Screws</b>				
FHB-1025-14SS	Single Stainless Steel Housing Bracket Kit to suit 10" Housing with ¼" Ports			
FHB-1025-34SS	Stainless Steel Housing Bracket Kit to suit 10" Housings with ½" & ¾" Ports			
FHB-1025-14DW	Double White Steel Housing Bracket Kit to suit 10" Housings with ¼" Ports			
FHB-1025-34DW	Double White Steel Housing Bracket Kit to suit 10" Housings with ½" & ¾" Ports			
FHB-1025-14TW	Triple Whites Steel Housing Bracket Kit to suite 10" Housings with ¼" Ports			
<b>Housing Spanners</b>				
FHS-SW1	Housing Spanner to suit ¼" Port Housings			
FHS-SW2	Housing Spanner to suit ¾" Port Housings			

Note: Flow rates are based on clean water without a cartridge. Please check cartridge flow rates to determine flows