

## Uniflow® MXT-Series Food Service Filtration Systems

The MXT Series Food Service Filtration systems are suited to larger capacity applications for mixer taps and Commercial Kitchen Appliances including boiling & chilled water and ice machines.

With a wide range of specialty cartridges, the MXT Series has a broad application vista including Sediment, Carbon Block, Granular Activated Carbon, Scale Reduction, Softening and Demineralisation.

Unique to the MXT is the Quick Change, double O-ring sanitary connection and large 3/8" BSPF Ports for High Flow Rates

Choose from 12" and 15" cartridge sizes to suit application capacity

### Benefits

- High Flow rates suitable for Mixer Taps
- Wide range of applications
- Double O-ring Seal
- NSF Standard 42

### Applications

- Drinking Water Filtration
- Food Service
- Scale Reduction
- Softening & Deionising
- Chlorine Reduction



Order Code	Size	Micron Rating	Description	Max Flow	Capacity
240-KIT	½" BSP	1	MXT Series Filtration System – 1 Micron Includes: NR Valve, 12" Carbon Block 1 Micron Cartridge, Filter Head, Bracket & Screws	6.3 LPM	12 Months / 56,000 Litres
FQH-TWIN-KIT	½" BSP	1	MXT Series High Flow System – 10 Micron Includes: NR Valve, 12" Carbon Block 1 Micron Cartridges, Twin Filter Head & Bracket, Screws	14 LPM	6 Months/ 75,000 Litres
FQH-HB-KIT	½" BSP	-	MXT Series Head & Bracket Kit Includes: Head, Bracket, Screws, ½" BSP Connections	-	-
FQH-1240-S5	12" x 4.0"	5	12" Sediment Cartridge – 5 Micron	6.3 LPM	Unlimited
FQH-1240-B1	12" x 4.0"	1	12" Carbon Block – 1 Micron (Cyst Rated)	6.3 LPM	56,000 Litres
FQH-1240-B10	12" x 4.0"	10	12" Carbon Block – 10 Micron	6.3 LPM	37,000 Litres
FQH-1240-P1	12" x 4.0"	1	12" Carbon with Phosphate (Scale Reduction)	6.3 LPM	56,000 Litres
FQH-1240-P10	12" x 4.0"	10	12" Carbon with Phosphate (Scale Reduction)	6.3 LPM	37,000 Litres
FQH-1540-P10	15" x 4.0"	10	15" Carbon with Phosphate (Scale Reduction)	7.5 LPM	75,000 Litres
FQH-1240-R	12" x 4.0"	-	12" Softening Cartridge – Standard Capacity	6.3 LPM	23,000 Mg
FQH-1540-R	15" x 4.0"	-	15" Softening Cartridge – High Capacity	7.5 LPM	34,200 Mg
FQH-1540-MB	15" x 4.0"	-	15" Deionising Cartridge	7.5 LPM	13,000 Mg

Install MXT Cartridges only into appropriate housings and flush for a minimum of 5 minutes prior to use. Use only with microbiologically safe and adequately disinfected water supplies.