

Aquastream 20" Steam Combi-Oven Filter System

With durability and performance in mind, the Uniflow Industrial range of FDA approved housings offers a comprehensive solution for a wide range of filtration applications.

Manufactured from virgin polypropylene to exacting quality standards, these robust and reliable housings will not leach chemicals into the filtrate stream.

Available in both 10" and 20" lengths in both standard and large diameter configurations, most models include pressure release as standard.

All housings are supplied with Buna-N O-Ring as standard and suit DOE and SOE cartridges.

Maximum Temperature: 45°C
Maximum Pressure: 8 bar



Benefits

- Pure, freshly filtered, great tasting water
- Chlorine taste & odour removal
- Cyst & Lead reduction models
- Rainwater filtration

Applications

- Mains Water
- Rainwater system
- Lead reduction
- Cyst reduction



Order Code	Description
AFSD-2025-SR	Aquastream 20" Steam Combi-Oven Filter System: Filter Head & Bracket Kit, Cartridge, Multifunction Valve Chrome 'Arc' Tap and Tubing, boxed.
FCB-2025-10P	Replacement Carbon Block with Phosphate - 10 Micron
FPS-2025	Uniflow 20" x 2.5" Polyspun Sediment Filter - 5 Micron
Flush cartridges for a minimum of 5 minutes prior to use. Use only with microbiologically safe and adequately disinfected water supplies.	