

Uniflow® Filter Housing Systems

Uniflow filter housing systems are pre-assembled and tested to make installation easier and reduce labour costs significantly.

Quality Uniflow industrial housings are manufactured from pure polypropylene to ensure no leaching into the filtrate and most models are supplied standard with pressure release buttons to assist with purging air from the system.

Assembled with stainless steel fixings onto sturdy powdercoated steel bracketry as standard and each system includes a housing spanner and can be optioned with pressure gauges.

Benefits

- Quality industrial housings
- Pre-assembled and tested
- Wide range of configurations
- Suits DOE and SOE Cartridges

Applications

- Drinking Water
- Food Service
- Beverage Production
- Rain Water



Order Code	Size	Port (")	Height (mm)	Width (mm)	Depth (mm)	Max Flow
Single Housings						
FSS-1025-14	1 x 10"	¼	325	114	120	14
FSS-1025-34	1 x 10"	¾	365	130	145	38
FSS-2025-34	1 x 20"	¾	622	130	145	76
FSS-1045-1	1 x 10" LD	1	466	185	215	76
FSS-2045-1	1 x 20" LD	1	728	185	215	90
Double Housings						
FSD-1025-14	2 x 10"	¼	355	235	130	12
FSD-1025-34	2 x 10"	¾	360	245	170	35
FSD-2025-34	2 x 20"	¾	622	245	170	70
FSD-1045-1	2 x 10" LD	1	400	392	215	70
FSD-2045-1	2 x 20" LD	1	660	392	215	90
Triple Housings						
FST-1025-14	3 x 10"	¼	355	360	130	12
FST-1025-34	3 x 10"	¾	360	385	170	35
FST-2025-34	3 x 20"	¾	622	385	170	70
FST-1045-1	3 x 10" LD	1	400	590	215	70
FST-2045-1	3 x 20" LD	1	660	590	215	90

Note: Flow rates are based on clean water without a cartridge. Please check cartridge flow rates to determine flows